



Indoor Floormount Rack



Unisol Floor mount steel racks are having ventilated top and bottom cover with cut-out for cable access, Provision for Fans, and fan tray mounting. Unisol Floor mount racks are used to house for both networks as well as server equipment. Side panels partially vented/plain. Racks with 4 nos. of heavy-duty caster wheels along with adjustable legs/plinth. Common sizes available in Floor Standing racks are 17U, 22U, 27U, 32U, 36U, 42U.

FEATURES

- Zero setup time and rapid deployment of IT equipment
- 100% assured compatibility with all equipment.
- Provision to mount the cooling fans on the top panel
- Powder-coated finish with seven tank pre-treatment process
- Grounding & Bonding Options
- Lock & key option for security purpose with front- or rear-door access
- The layout of the cabinet is reasonable, which will facilitate cable access, fixing and grounding. At the bottom of the cabinet, there are entrance holes individually for power cable, signal cable and optical cable.
- The cabinet uses assembled structure, easy for installation.
- The cabinet includes 19" standard installation frame.
- Depth adjustable mounting slots.
- Precision engineering capabilities and best efficient software configuration product technology provide the best product quality and fastest delivery in the industry.
- Top and bottom Panel with ventilation and cable entry facility.
- Provision to mount the cooling fans on the top panel.

Telecommunications

Data Centers

Security Surveillance Applications

Office Environments

Server and comms rooms

Internet service providers and many more applications.



Indoor Floormount Rack

SPECIFICATIONS

Mounting	Floor Mountable
Material	Galvanized Steel
Basic Frame	Steel four pillars with the steel end frame
Construction	Welded
Front Door	Lockable GI Door Plain or Lockable Toughened Glass GI Door
Standard Finish	Powder Coating
Standard Mounting Option	Castor wheels with leverels / base frame
Standard Color	Light Grey / Dark Grey
Top and Bottom Panel	Welded, with necessary ventilation and Cable entry cut-outs

DIMENSIONS

	H	W	D	PART NO.
17U	955mm	600mm	650mm 700mm 850mm 1000mm	UCPL-IDFM-17U
22U	1175mm	600mm	650mm 700mm 850mm 1000mm	UCPL-IDFM-22U
27U	1340mm	600mm	650mm 700mm 850mm 1000mm	UCPL-IDFM-27U
32U	1620mm	600mm	650mm 700mm 850mm 1000mm	UCPL-IDFM-32U
36U	1780mm	600mm	650mm 700mm 850mm 1000mm	UCPL-IDFM-36U
42U	2070mm	600mm	650mm 700mm 850mm 1000mm	UCPL-IDFM-42U